

ImagePerfect™ 3200 Promotional Film

ImagePerfect™ 3200 Promotional Film is a high-quality, short-term, gloss vinyl range with a permanent, advanced water-based adhesive. This range is available in 50 colours, including black, white and clear, with black and white also available with a removable, advanced water-based adhesive.

ImagePerfect™ 3200 Promotional Film is suitable for a wide variety of indoor and short-term outdoor applications, such as general purpose signage, exhibition graphics, decorative panels, directional signage, point-of-sale displays, fleet marking (flat panel), public transport advertising (flat panel), etc. The specially-formulated, flexible films and high-quality silicone liner ensure that the films can be cut easily and weeded quickly. A permanent, advanced water-based adhesive creates a strong final bond to ensure a secure and durable finish. Black and white are also available with a removable, advanced water-based adhesive that creates a reasonable final bond to ensure a secure finish whilst retaining removability. This product range is compatible with wet application.

Specifications	
Description	Promotional film
Colour	50 colours (gloss), including black, white and clear
Thickness	75µ
Adhesive	Advanced acrylic, permanent (black and white also available in removable)
Adhesive Strength	18N/25mm (Finat TM 1/24h) ± 2N
Release Paper	One-sided siliconised, clay-coated kraft, 120g/m ²
Temperature Range	-30°C to +90°C
Durability (unprinted)	5 years (black and white) 3 years (clear, colours and metallics)
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© December 2020 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading. Spandex gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Spandex's general terms and conditions of sale. Spandex's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Spandex be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.