

ImagePerfect™ 3000 Promotional Film is a quality gloss vinyl range with a permanent, acrylic adhesive. This range is available in black, white, clear and 15 colours. Black, white and clear is also available with removable adhesive.

IP 3000

ImagePerfect™ 3000 Promotional Film is suitable for a wide variety of indoor and some short-life outdoor applications, such as general purpose signage, decorative panels, directional signage, short-life outdoor advertising, fleet marking, public transport advertising, etc. The vinyls are specially-formulated, flexible, films to enable them to cut easily and weed quickly. A permanent, repositionable, acrylic adhesive with low initial tack allows for easy repositioning during application. The ultimate strong bond ensures a secure and durable finish and the inherent properties of the products promote excellent cutting and weeding characteristics because of the high-quality Kraft liner. For white vinyl, a light blue Kraft liner is used to form a stronger contrast to lettering.

Specifications	
DESCRIPTION	Promotional Film, gloss
COLOUR	Black, white, clear and 15 colours
THICKNESS	75µ
ADHESIVE	Permanent, acrylic adhesive (black, white and clear also available in semi-permanent)
ADHESIVE STRENGTH	16N/25mm (Finat TM 1/24h) with permanent adhesive 12N/25mm (Finat TM 1/24h) with semi-permanent adhesive
RELEASE PAPER	One-sided siliconised, clay-coated Kraft, 125g/m ² , white vinyl with blue contrast liner
TEMPERATURE RANGE	- 30°C up to + 90°C
DURABILITY (UNPRINTED)	4 years (white and black) 3 years (clear, colours and metallics)
FLAME RETARDANCY	B1
SHELF LIFE	2 years, 20°C / 50% humidity

© January 2013 Spandex Group. Technical specifications subject to change without prior notice.
All trademarks mentioned are property of their respective owners.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased. Also for horizontal applications, exterior performance will be decreased.

Distributed by Spandex. www.spandex.com

Spandex UK, 1600 Park Avenue, Aztec West, Almondsbury, Bristol BS32 4UA
Tel. +44 (0)1454 616 444 | Fax +44 (0)1454 616 777 | www.spandex.com

